



# revo

paint + primer in one  
Premium Eggshell Finish 16 Series

**PRODUCT DATA**

**GENERIC TYPE:** Vinyl Acetate Copolymer Modified Acrylic

**DESCRIPTION:** REVO Paint + Primer in One Premium Interior Eggshell/Satin Finish is a, high-hiding, self-priming wall paint specifically formulated to provide superior durability with excellent coverage and application properties.

**Features:**

- Paint + Primer in One
- GREEN WISE® Certified
- Low Odor / Zero VOC
- Hides Imperfections
- Excellent Flow & Leveling

**RECOMMENDED USES:** REVO dries to a beautiful, washable finish that is ideal for both residential and commercial applications where a tough coating is desired. Ideal for hallways, kitchens, bathrooms, and other hard use areas, such as architectural woodwork, doors, trim and cabinets. Us on properly prepared new or previously painted interior drywall, plaster, and masonry.

**COMPATIBLE COATINGS:** May be applied over properly prepared latex or alkyd/oil finishes. See application instructions for proper substrate primer.

**Primers:** Self prime or

- McCormick uniX Multi-Purpose and Stain Blocking Interior/Exterior Primer 06460.
- McCormick Underlok Interior/Exterior Acrylic Latex Multi-Purpose Primer 06452.
- McCormick Permalok Interior/Exterior 100% Acrylic Masonry Primer 06451.
- McCormick Underlok Acrylic Metal Primer 06449.

**PHYSICAL CHARACTERISTICS**

**Colors:** Full Range

**Vehicle Type:** Vinyl Acetate Copolymer

**VOC/VOS:** < 10 g/L VOC

**Volume Solids (Avg.):** 41%± 2%

**Weight Solids (Avg.):** 60%± 2%

**Viscosity:** 95 KU

**Suggested Film Thickness:**

3.0-4.0 mils wet, 1.25-1.65 mils dry

**Theoretical Coverage per Gallon:**

350 sq. ft. @ 1.25-1.65 mils DFT

**Gloss Level:** 5-8 units @ 60°

**Sheen:** 8-15 units @ 85°

**Drying Time @ 77°F & 50% R.H.:**

**To Touch:** 30 Minutes

**Recoat:** 4 hours. Allow additional drying time during humid or cooler weather.

**Min. Surface/Air Temperature at Application:** 50°F

**Max. Surface/Air Temperature at Application:** 110°F

**Flash Point:** N/A

**Heat Resistance:** 150°F Intermittent

**Application:** Brush, Roller, or Spray

**Thinning:**

**Brush and Roller:** Not Recommended

**Spray:** Up to One Pint of Water per Gallon

**Clean Up:** Warm Water and Detergent

**Packaging:** Quart, Gallon and Five Gallon

**Weight per Gallon:** 11.9-12.1 lb./gal

**NOT RECOMMENDED:** Do not paint over wallcoverings. Vinyl wallcoverings can lose adhesion through age or from new or previous paint applications.



≤ 50 g/L

GREEN WISE®	LEED	SCAQMD	OTC
YES	YES	YES	YES

## APPLICATION INSTRUCTIONS

For the following surfaces, prime as indicated and finish with two (2) coats of McCormick REVO™ Premium Eggshell/Satin Finish.

### SURFACE PREPARATION:

**Previously Painted Surfaces:** The surface must be clean and dry. Remove dirt, grease, calcimine, wallpaper paste, loose paint, and any other foreign matter. Cracks should be spackled and allowed to dry. Scuff glossy areas by sanding. Use the self-priming properties of REVO and apply one coat to any repaired or uncoated surfaces and allow to dry. Then apply two coats of REVO. For severe stains, water marks or other challenging conditions, use Underlok Interior/Exterior Acrylic Latex Multi-Purpose Primer 06452.

### Unpainted Surfaces: Self-Prime or Prime -

**Drywall:** uniX Multi-Purpose and Stain Blocking Interior/Exterior Primer 06460.

**Plaster:** Allow new plaster to age 30 days. Prime with Permalok Interior/Exterior 100% Acrylic Masonry Primer 06451.

**Wood:** uniX Multi-Purpose and Stain Blocking Interior/Exterior Primer 06460.

**Masonry:** Permalok Interior/Exterior 100% Acrylic Masonry Primer 06451.

**Block:** Interior/Exterior Latex Block Filler 01015.

**Unpainted Galvanized Metal:** Clean new galvanized surfaces by wiping surface with clean rags wet with mineral spirits. Prime with McCormick Underlok Acrylic Metal Primer 06449.

### APPLICATION:

Always stir well before use. Additives for ease of application or to promote adhesion are not recommended. Do not apply if material, substrate, or ambient temperature is below 50°F or above 110°F. Relative humidity should be below 90%. Apply by brush, roller, or spray. For best brush application results, use a quality synthetic filament brush. For roller application, use a 3/8" to 1/2" nap cover. For spray application, thin with clean water, up to one pint per gallon if necessary.

### WASHING INSTRUCTIONS:

Allow 30 days after application before washing. Remove common dirt stains by using a soft cloth or sponge, warm water and mild detergent. Do not apply too much hand pressure during washing; this will cause paint to burnish causing discoloration.

### APPLICATION EQUIPMENT:

Rev Date 03/24

- Apply by brush, roller, or spray.
- Manufacturers listed below are a guide. Others may be used. Changes in pressure and tip size may be required to achieve proper application.

#### Airless Spray:

Pump: Graco / Titan

High Pressure Filter: 60 Mesh

Fluid Hose: 1/4" x 50'

Tips: 0.015" - 0.021"

Minimum pressure to avoid fingering: 2000 psi

### CAUTIONS --- Lead Hazard: WARNING!

If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

### CAUTION - CONTAINS CRYSTALLINE SILICA IN AN ENCAPSULATED STATE:

If the dry paint film is sanded, the dust emitted can contain crystalline silica which has been shown to cause cancer under long term exposure. **USE ONLY WITH ADEQUATE VENTILATION.** Wear appropriate respiratory protection when sanding or spraying this product. To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, wear respiratory protection (NIOSH/MSHA TC23C or equivalent) or leave the area. Avoid contact with eyes and skin.

**FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

**CONTAINER LABELING COMPLIES WITH APPLICABLE STATE RIGHT-TO-KNOW ACTS.** For additional safety and health information, please refer to the Safety Data Sheet (SDS).

MANUFACTURED BY:

**McCormick Paints**  
THE PAINT THE PROS USE

11200 Rockville Pike, Suite 504 Rockville MD 20852

Technical Service 1-877-PAINT-55 — Ph: 301-770-3235 — Fax: 301-770-9814

[www.mccormickpaints.com](http://www.mccormickpaints.com)